

ConCar

Klassische Keilriemen DIN 2215/ ISO 4184 - ummantelt
 Classical Section V - Belts DIN 2215/ ISO 4184 - wrapped

Profil/ Section B / 17 x 11 mm			Profil/ Section B / 17 x 11 mm		
Code - Nr.	Richtlänge pitch length ISO / LD mm	Innenlänge inside length mm	Code - Nr.	Richtlänge pitch length ISO / LD mm	Innenlänge inside length mm
B 22 1/2	610	570	B 63	1640	1600
B 24	655	615	B 64	1665	1625
B 25	670	630	B 65	1690	1650
B 25 1/2	690	650	B 66	1716	1676
B 26 1/2	710	670	B 67	1740	1700
B 27	726	686	B 68	1765	1725
B 28	750	710	B 69	1790	1750
B 28 1/2	765	725	B 69 1/2	1801	1761
B 29 1/2	790	750	B 70	1815	1775
B 30	802	762	B 71	1840	1800
B 30 1/2	815	775	B 72	1869	1829
B 31	827	787	B 73	1890	1850
B 31 1/2	840	800	B 74	1920	1880
B 32	853	813	B 75	1940	1900
B 32 1/2	865	825	B 76	1970	1930
B 33	876	836	B 77	1990	1950
B 33 1/2	890	850	B 78	2021	1981
B 34	904	864	B 79	2040	2000
B 34 1/2	915	875	B 80	2072	2032
B 35	929	889	B 81	2100	2060
B 35 1/2	940	900	B 82	2123	2083
B 36	954	914	B 83	2140	2100
B 36 1/2	965	925	B 83 1/2	2160	2120
B 37	980	940	B 84	2170	2130
B 37 1/2	990	950	B 85	2200	2160
B 38	1005	965	B 86	2225	2185
B 38 1/2	1015	975	B 86 1/2	2240	2200
B 39	1030	990	B 87	2550	2210
B 39 1/2	1040	1000	B 88	2280	2240
B 40	1056	1016	B 89	2300	2260
B 40 1/2	1070	1030	B 90	2326	2286
B 41	1080	1040	B 90 1/2	2340	2300
B 41 1/2	1090	1050	B 91	2350	2310
B 42	1100	1060	B 92	2370	2330
B 42 1/2	1115	1075	B 93	2400	2360
B 43	1130	1090	B 94	2420	2380
B 43 1/2	1140	1100	B 94 1/2	2440	2400
B 44	1160	1120	B 95	2453	2413
B 45	1190	1150	B 96	2478	2438
B 45 1/2	1203	1163	B 96 1/2	2490	2450
B 46	1215	1175	B 97	2505	2465
B 46 1/2	1220	1180	B 98	2530	2490
B 47	1230	1190	B 98 1/2	2540	2500
B 47 1/2	1240	1200	B 99	2560	2520
B 48	1255	1215	B 100	2580	2540
B 48 1/2	1265	1225	B 101	2610	2570
B 49	1290	1250	B 102	2640	2600
B 50	1315	1275	B 103	2665	2625
B 51	1340	1300	B 104	2690	2650
B 52	1360	1320	B 105	2707	2667
B 52 1/2	1375	1335	B 106	2740	2700
B 53	1390	1350	B 108	2790	2750
B 53 1/2	1400	1360	B 110	2840	2800
B 54	1412	1372	B 112	2885	2845
B 55	1440	1400	B 114	2940	2900
B 56	1462	1422	B 116	2990	2950
B 57	1490	1450	B 118	3040	3000
B 58	1513	1473	B 120	3088	3048
B 59	1540	1500	B 122	3140	3100
B 60	1565	1525	B 124	3190	3150
B 59	1540	1500	B 126	3240	3200
B 60	1565	1525	B 128	3290	3250
B 61	1590	1550	B 130	3340	3300
B 62	1615	1575	B 132	3390	3350

Gewicht/ weight = 0,198 kg/m

ConCar

Klassische Keilriemen DIN 2215/ ISO 4184 - ummantelt
Classical Section V - Belts DIN 2215/ ISO 4184 - wrapped

Profil/ Section B / 17 x 11 mm

Code - Nr.	Richtlänge pitch length ISO / LD mm	Innenlänge inside length mm				
B 134	3440	3400				
B 135	3470	3430				
B 136	3490	3450				
B 138	3540	3500				
B 140	3590	3550				
B 142	3640	3600				
B 144	3698	3658				
B 146	3740	3700				
B 148	3790	3750				
B 151 1/2	3890	3850				
B 155 1/2	3990	3950				
B 157 1/2	4040	4000				
B 162	4155	4115				
B 165	4240	4200				
B 167	4290	4250				
B 173	4435	4395				
B 175	4490	4450				
B 177	4540	4500				
B 180	4612	4572				
B 187	4790	4750				
B 192	4915	4875				
B 195	4993	4953				
B 197	5040	5000				
B 208 1/2	5340	5300				
B 210	5374	5334				
B 220 1/2	5640	5600				
B 236	6040	6000				
B 248	6340	6300				
B 256	6540	6500				
B 264	6740	6700				
B 276	7040	7000				
B 279 1/2	7140	7100				