

ConCar

[zurück zu Se](#)

Hochleistungs - Schmalkeilriemen Rex - flankenoffen, formgezahnt
 High Capacity Narrow V-Belts Rex - raw edge, moulded cogged

XPZ AVX 10/9,5		XPZ AVX 10/ 9,5		XPA AVX 13/ 12,5	
LW/LD= Richtlänge pitch length mm	LA= Außenlänge outside length mm	LW/LD= Richtlänge pitch length mm	LA= Außenlänge outside length mm	LW/LD= Richtlänge pitch length mm	LA= Außenlänge outside length mm
562	575	1262	1275	582	600
587	600	1287	1300	657	675
592	605	1312	1325	682	700
602	615	1320	1333	707	725
612	625	1327	1340	732	750
622	635	1337	1350	757	775
630	643	1362	1375	782	800
637	650	1387	1400	800	818
662	675	1400	1413	807	825
670	685	1412	1425	832	850
682	695	1437	1450	850	868
687	700	1462	1475	857	875
697	710	1487	1500	882	900
710	725	1500	1513	900	918
717	730	1512	1525	907	925
722	735	1537	1550	932	950
737	750	1562	1575	950	968
750	763	1587	1600	957	975
762	775	1600	1613	982	1000
772	785	1612	1625	1000	1018
787	800	1637	1650	1007	1025
800	813	1662	1675	1012	1030
812	825	1687	1700	1032	1050
825	838	1700	1713	1042	1060
837	850	1737	1750	1060	1075
850	864	1750	1763	1082	1100
857	870	1762	1775	1107	1125
862	875	1787	1800	1120	1138
875	888	1800	1813	1132	1150
887	900	1887	1900	1157	1175
892	905	1900	1913	1180	1200
900	913	1937	1950	1207	1225
912	925	2000	2013	1232	1250
917	930	2037	2050	1250	1268
922	935	2120	2133	1257	1275
925	940	2240	2253	1282	1300
937	950	2360	2373	1307	1325
947	960	2500	2513	1320	1338
950	965	2650	2663	1332	1350
957	970	2800	2813	1357	1375
962	975	3000	3013	1382	1400
967	980	3150	3163	1400	1418
977	990	3350	3363	1407	1425
987	1000	3550	3563	1432	1450
992	1005			1457	1475

1000	1013			1482	1500
1012	1025			1500	1518
1037	1050			1507	1525
1047	1060			1532	1550
1060	1075			1557	1575
1077	1090			1582	1600
1087	1100			1600	1618
1112	1125			1607	1625
1120	1133			1632	1650
1137	1150			1657	1675
1152	1165			1682	1700
1162	1175			1700	1718
1180	1193			1707	1725
1187	1200			1732	1750
1202	1215			1757	1775
1212	1225			1782	1800
1237	1250			1800	1818
1250	1263			1807	1825
Gewicht/ weight = 0,065 kg/m				Gewicht/ weight = 0,111 kg/m	

ConCar

Hochleistungs - Schmalkeilriemen Rex - flankenoffen, formgezahnt
High Capacity Narrow V-Belts Rex - raw edge, moulded cogged

XPA \ VX 13/ 12,5		Profil/ Section XPB / 5VX		Profil/ Section XPC	
LW/LD= Richtlänge pitch length mm	LA= Außenlänge outside length mm	LW/LD= Richtlänge pitch length mm	LA= Außenlänge outside length mm	LW/LD= Richtlänge pitch length mm	LA= Außenlänge outside length mm
1832	1850	1250	1272	2000	2030
1857	1875	1320	1342	2120	2150
1882	1900	1400	1422	2240	2270
1900	1918	1450	1472	2360	2390
1907	1925	1500	1522	2500	2530
1932	1950	1525	1547	2650	2680
1950	1968	1550	1572	2800	2830
1957	1975	1600	1622	3000	3030
1982	2000	1650	1672	3150	3180
2000	2018	1700	1722	3350	3380
2007	2025	1750	1772	3450	3480
2032	2050	1800	1822	3550	3580
2057	2075	1900	1922	3750	3780
2082	2100	1930	1952	4000	4030
2120	2138	1950	1972	4100	4130
2132	2150	2000	2022	4250	4280
2157	2175	2020	2042	4500	4530
2182	2200	2120	2142	4750	4780
2232	2250	2180	2202	5000	5030
2240	2258	2240	2262	5300	5330
2307	2325	2360	2382	5600	5630
2360	2378	2410	2432	6000	6030
2382	2400	2500	2522		
2432	2450	2530	2552		
2464	2482	2650	2672		
2482	2500	2680	2702		

2500	2518	2710	2732			
2650	2668	2800	2822			
2800	2818	2840	2862			
3000	3018	2900	2922			
3150	3168	3000	3022			
3350	3368	3150	3172			
3550	3568	3250	3272			
3750	3768	3350	3372			
4000	4018	3450	3472			
		3550	3572			
		3750	3772			
		3800	3822			
		4000	4022			
		4250	4272			
		4500	4522			
		4750	4772			
		5000	5022			
		5300	5322			
		5600	5622			
		6000	6022			
		6700	6722			
		5VX 560	1422			
		5VX 630	1600			
		5VX 710	1803			
		5VX 1500	3810			
		5VX 1600	4064			
		5VX 1700	4318			
		5VX 1800	4572			
		5VX 1900	4826			
		5VX 2000	5080			
Gewicht/ weight = 0,111 kg/m		Gewicht/ weight = 0,183 kg/m		Gewicht/ weight = 0,340 kg/m		

ite 1